



AAT 505

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Issue date: 8/22/2024 Revision date: 8/22/2024 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : AAT 505
Product code : 505

1.2. Recommended use and restrictions on use

Recommended use : Automotive Care Products, Polishes and wax blends
Restrictions on use : None known

1.3. Supplier

3D International
20724 Centre Pointe Pkwy #1
Santa Clarita, CA 91350
T 888-999-7627

1.4. Emergency telephone number

Emergency number : (Chemical Spills, Leaks, Fire, Exposure or Accident only)
CHEMTREC 1-800-424-9300 (in the US & Canada)
1-703-527-3887 (Outside the US)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Not classified

2.2. GHS Label elements, including precautionary statements

GHS US labeling

No labeling applicable

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None known.

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	10 - 30

AAT 505

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Name	Product identifier	%
Aluminum Oxide	CAS-No.: 1344-28-1	10 - 15
Glycerin	CAS-No.: 56-81-5	1 – 5
Propan-2-ol, isopropyl alcohol, isopropanol	CAS-No.: 67-63-0	1 – 5
White Mineral Oil (Petroleum)	CAS-No.: 8042-47-5	1 – 5

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: No first aid should be needed.
First-aid measures after skin contact	: Wash with soap and water. Seek medical attention if irritation develops.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Get medical attention if irritation develops and persists.
First-aid measures after ingestion	: Rinse mouth out with water. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Inhalation	: May cause minor irritation to the respiratory tract and to other mucous membranes.
Skin	: May cause slight irritation to the skin.
Eyes	: May cause minor eye irritation.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Most Important Symptoms/Effects	: Not expected to present a significant hazard under anticipated conditions of normal use. May cause minor eye irritation. May cause slight irritation to the skin.
Chronic symptoms	: None known.

4.3. Immediate medical attention and special treatment, if necessary

Not required.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: None.

5.2. Specific hazards arising from the chemical

Fire hazard	: This product is not classified as flammable or combustible.
Hazardous decomposition products in case of fire	: Carbon oxides (CO, CO2).

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Wear suitable protective clothing. Avoid contact with eyes, skin and clothing.
------------------	--

6.1.1. For non-emergency personnel

Emergency procedures	: Keep unnecessary and unprotected personnel away from the spillage.
----------------------	--

AAT 505

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container.

Other information : Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes, skin and clothing.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : No special storage required.

Incompatible materials : None known.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

USA - ACGIH - Occupational Exposure Limits

Local name	2-Propanol
ACGIH OEL TWA	200 ppm
ACGIH OEL STEL	400 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2024

USA - ACGIH - Biological Exposure Indices

Local name	2-Propanol
BEI (BLV)	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B, Ns
Regulatory reference	ACGIH 2024

USA - OSHA - Occupational Exposure Limits

Local name	Isopropyl alcohol
------------	-------------------

AAT 505

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
OSHA PEL (TWA)	980 mg/m ³ 400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Distillates (petroleum), hydrotreated light (64742-47-8)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Mineral oil, excluding metal working fluids Pure, highly and severely refined
ACGIH OEL TWA	5 mg/m ³ (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Oil mist, mineral
OSHA PEL (TWA)	5 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Aluminum Oxide (1344-28-1)	
USA - OSHA - Occupational Exposure Limits	
Local name	alpha-Alumina
OSHA PEL (TWA)	15 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Glycerin (56-81-5)	
USA - OSHA - Occupational Exposure Limits	
Local name	Glycerin (mist)
OSHA PEL (TWA)	15 mg/m ³ (Total dust) 5 mg/m ³ (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
White Mineral Oil (Petroleum) (8042-47-5)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Mineral oil, excluding metal working fluids Pure, highly and severely refined
ACGIH OEL TWA	5 mg/m ³ (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Oil mist, mineral
OSHA PEL (TWA)	5 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : No particular/specific measures required.
Environmental exposure controls : Avoid release to the environment.

AAT 505

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Not required for normal conditions of use. Protective gloves recommended. Handling product in bulk: Wear suitable gloves

Eye protection:

Avoid contact with eyes

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Not required for normal conditions of use. In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

Thermal hazard protection:

Not applicable.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Green. Liquid.
Color	: Green
Odor	: Fruity
Odor threshold	: No data available
pH	: 8
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1.035
Solubility	: In water, material is partially soluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 3370 mm²/s 40°C
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: None.
Oxidizing properties	: None.

9.2. Other information

No additional information available

AAT 505

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

LD50 oral rat	5840 mg/kg
LD50 dermal rabbit	16.4 ml/kg
LC50 Inhalation - Rat [ppm]	1666.66 ppm/1h

Distillates (petroleum), hydrotreated light (64742-47-8)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat (Vapours)	> 5.28 mg/l/4h

Aluminum Oxide (1344-28-1)

LD50 oral rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 7.6 mg/l 1 h

Glycerin (56-81-5)

LD50 oral rat	27200 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Female, Experimental value, Oral)
LD50 oral	25000 mg/kg body weight
LD50 dermal	56750 mg/kg (4 day(s), Guinea pig, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat (Dust/Mist)	> 5.85 mg/l

AAT 505

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

White Mineral Oil (Petroleum) (8042-47-5)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	> 5 mg/l/4h No mortality

Skin corrosion/irritation	: Not classified. pH: 8
Serious eye damage/irritation	: Not classified pH: 8
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified

Distillates (petroleum), hydrotreated light (64742-47-8)

NOAEL (animal/male, F0/P)	≥ 3000 mg/kg body weight (rat)
---------------------------	--------------------------------

Aluminum Oxide (1344-28-1)

NOAEL (animal/male, F0/P)	1000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
STOT-single exposure	: Not classified.

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Distillates (petroleum), hydrotreated light (64742-47-8)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

Distillates (petroleum), hydrotreated light (64742-47-8)

NOAEL (oral,rat,90 days)	750 mg/kg body weight
--------------------------	-----------------------

Aluminum Oxide (1344-28-1)

NOAEC (inhalation,rat,dust/mist/fume,90 days)	0.07 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
---	---

White Mineral Oil (Petroleum) (8042-47-5)

NOAEL (oral,rat,90 days)	≥ 1200 mg/kg body weight
--------------------------	--------------------------

Aspiration hazard	: Not classified
Viscosity, kinematic	: 3370 mm²/s 40°C

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

Viscosity, kinematic	2.58 mm²/s
----------------------	------------

Distillates (petroleum), hydrotreated light (64742-47-8)

Viscosity, kinematic	1 – 2.4 mm²/s at 20°C
----------------------	-----------------------

Hydrocarbon	Yes
-------------	-----

AAT 505

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Glycerin (56-81-5)

Viscosity, kinematic	1119.746 mm ² /s
----------------------	-----------------------------

White Mineral Oil (Petroleum) (8042-47-5)

Viscosity, kinematic	> 3 mm ² /s
----------------------	------------------------

Hydrocarbon	Yes
-------------	-----

Inhalation	: May cause minor irritation to the respiratory tract and to other mucous membranes.
Skin	: May cause slight irritation to the skin.
Eyes	: May cause minor eye irritation.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Most Important Symptoms/Effects	: Not expected to present a significant hazard under anticipated conditions of normal use. May cause minor eye irritation. May cause slight irritation to the skin.
Chronic symptoms	: None known.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: No toxicity data available for product. This product is expected to be harmful to the aquatic environment. Releases to the environment should be avoided. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
-------------------	---

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)

LC50 - Fish [1]	10000 mg/l Pimephales promelas (Fathead minnow)
-----------------	---

EC50 - Crustacea [1]	> 10000 mg/l
----------------------	--------------

LC50 - Fish [2]	9640 mg/l Pimephales promelas (Fathead minnow)
-----------------	--

NOEC chronic crustacea	3.37 mg/l
------------------------	-----------

Distillates (petroleum), hydrotreated light (64742-47-8)

LC50 - Fish [1]	2 mg/l
-----------------	--------

EC50 - Crustacea [1]	1.4 mg/l
----------------------	----------

EC50 72h - Algae [1]	3.7 mg/l
----------------------	----------

Aluminum Oxide (1344-28-1)

EC50 72h - Algae [1]	1.05 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
----------------------	---

EC50 72h - Algae [2]	0.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
----------------------	--

Glycerin (56-81-5)

LC50 - Fish [1]	54000 mg/l (96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Lethal)
-----------------	--

EC50 - Crustacea [1]	> 10000 mg/l (24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
----------------------	--

EC50 - Other aquatic organisms [1]	> 10000 mg/l waterflea
------------------------------------	------------------------

EC50 - Other aquatic organisms [2]	> 10000 mg/l
------------------------------------	--------------

White Mineral Oil (Petroleum) (8042-47-5)

LC50 - Fish [1]	> 100 mg/l
-----------------	------------

EC50 - Crustacea [1]	> 100 mg/l
----------------------	------------

AAT 505

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

12.2. Persistence and degradability

AAT 505	
Persistence and degradability	No additional information available.
Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
Persistence and degradability	Readily biodegradable.
Distillates (petroleum), hydrotreated light (64742-47-8)	
Persistence and degradability	Inherently biodegradable.
Aluminum Oxide (1344-28-1)	
Persistence and degradability	Biodegradation is not applicable to inorganic compounds.
Glycerin (56-81-5)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.87 g O ₂ /g substance
Chemical oxygen demand (COD)	1.16 g O ₂ /g substance
ThOD	1.217 g O ₂ /g substance
BOD (% of ThOD)	0.71
White Mineral Oil (Petroleum) (8042-47-5)	
Persistence and degradability	Inherently biodegradable.

12.3. Bioaccumulative potential

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
BCF - Fish [1]	3
Partition coefficient n-octanol/water (Log Kow)	0.05
Glycerin (56-81-5)	
Partition coefficient n-octanol/water (Log Pow)	-1.75 (Experimental value, Equivalent or similar to OECD 107, 25 °C)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.5
Glycerin (56-81-5)	
Surface tension	0.0634 N/m (20 °C, 1000 g/l)
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

No additional information available

AAT 505

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Dispose of in accordance with applicable federal, state, and local regulations.
Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
The product is shipped unregulated because it is packaged in either single packages or a combination of inner packagings containing net quantities of less than 5 kg/5 L (IMDG Code 2.10.2.7; ICAO Special Instruction A197, 49CFR 171.4(c)(2)). Shipment may be regulated if contents are removed from inner packaging and combined into containers exceeding 5kg or 5L.			

14.6. Special precautions for user

DOT
Not regulated

TDG
Not regulated

IMDG
Not regulated

IATA
Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

AAT 505

SARA Section 311/312 Hazard Classes	Refer to Section 2 for OSHA Hazard Classification.
-------------------------------------	--

AAT 505

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Aluminum Oxide	CAS-No. 1344-28-1	10 - 15%
----------------	-------------------	----------

15.2. International regulations

No additional information available

15.3. US State regulations

 **WARNING:** This product can expose you to Diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Propan-2-ol, isopropyl alcohol, isopropanol(67-63-0)	U.S. - New Jersey - Right to Know Hazardous Substance List
Aluminum Oxide(1344-28-1)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - New Jersey - Right to Know Hazardous Substance List
Glycerin(56-81-5)	U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Revision date : 8/22/2024

Data sources : This safety data sheet was compiled with data and information from the following sources : RTECS, ECOSAR, HSDB, SIDS SIAP, CESAR, Chemical DB.

Indication of changes:

new version.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.